



Bases unipolares abiertas para DC

1 Pole DC fuse bases

A 160|200|250|400|450|630

Gama / Range

Referencia Reference	Terminales Terminals	Tamaño Size	Tensión Voltage	Intensidad Current
434.16.111.02.X	M10	NH 1	1000 V DC	200 A
434.1B.111.02.X	M10	NH 2	1000 V DC	250 A
434.14.111.02.X	M10	NH 1XL	1100 V DC	250 A
	M10	NH 1XL	1500 V DC	200 A
434.1A.111.02.X	M10	NH 2XL	1100 V DC	400 A
	M10	NH 2XL	1500 V DC	250 A
434.15.111.02.X	M10	NH 3L	1100 V DC	630 A
	M10	NH 3L	1500 V DC	450 A
434.15.117.18.0	M12	NH 2XL/3 L	1100 V DC	630 A
	M12	NH 2XL/3 L	1500 V DC	450 A
434.15.117.YY.X	M12	NH 3 L	1500 V DC	630 A

X = 0 Base portafusibles / Fuse base

X = 5 Base portafusibles protegida (cubrecontactos aislante) / Protected fuse base (insulating contact covers)

X = 7 Base portafusibles protegida (cubrecontactos aislante + separador ancho) / Protected fuse base (insulating contact covers + wide separator)

